

11

will clearly understand that many modifications are possible in the preferred embodiment without departing from the teachings thereof. All such modifications are intended to be encompassed within the following claims.

I claim:

1. A data collection method for scanning a scan window comprising one or more channels comprising the steps of: detecting an integrated signal (S) across a scan window comprising one or more channels using an integrating detector; and calculating a velocity-normalized integrated signal (S_n) as a function of a scan velocity and the integrated signal S.
2. The method of claim 1 wherein the step of calculating the velocity-normalized integrated signal (S_n) comprises: determining a scan velocity, v; and dividing the integrated signal S by the scan velocity v.
3. The method of claim 1 wherein the step of calculating the velocity-normalized integrated signal (S_n) comprises: measuring a channel width (w); determining a time for traversing the channel width (t); and computing a velocity-normalized integrated signal according to the equation $S_n = S/(w/t)$.
4. The method of claim 1 wherein the step of calculating the velocity-normalized integrated signal (S_n) comprises subtracting a detector offset S_o from an integrated signal (S).
5. The method of claim 1 wherein the channels are disposed in a linear array.
6. The method of claim 1 wherein the channels are lanes in a multilane electrophoresis system.
7. The method of claim 6 wherein the lanes are located in a slab gel.
8. The method of claim 6 wherein the lanes are located in isolated electrophoresis channels.
9. The method of claim 6 wherein the lane density of the multilane electrophoresis system is at least 1.8 mm/lane.
10. The method of claim 1 wherein the step of detecting an integrated signal across a scan window is effected using a stepper motor to cause a relative motion between the scan window and the integrating detector.
11. The method of claim 10 wherein a channel width (w) is measured by counting steps in the stepper motor.
12. The method of claim 11 wherein a position sensor is used to define a home position for initializing the stepper motor.
13. The method of claim 1 wherein the integrating detector is a CCD or a photodiode array.
14. The method of claim 1 wherein the integrated signal results from detection of a fluorescence emission.
15. The method of claim 14 wherein the fluorescence emission is stimulated by a laser.
16. An apparatus for scanning a plurality of channels comprising:

12

means for detecting an integrated signal (S) across a scan window comprising one or more channels using an integrating detector; and

computer means for receiving the integrated signal S and determining a scan velocity and for calculating a velocity-normalized integrated signal (S_n) as a function of the scan velocity and the integrated signal S.

17. An apparatus for scanning a scan window having one or more channels comprising:

an integrating detector;

a scanner for effecting a scanning of the integrating detector relative to a scan window comprising one or more channels; and

a computer for receiving the integrated signal S and for determining a scan velocity and for calculating a velocity-normalized integrated signal (S_n).

18. The apparatus of claim 17 wherein the integrating detector is a charged coupled device.

19. The apparatus of claim 17 wherein the scanner comprises a stepper motor.

20. The apparatus of claim 17 wherein the scan window comprises multiple electrophoresis lanes.

21. A program storage device readable by a machine, tangibly embodying a program of instructions executable by a machine to perform method steps to scan a scan window comprising one or more channels, said method steps comprising:

detecting an integrated signal (S) across a scan window comprising one or more channels using an integrating detector; and

calculating a velocity-normalized integrated signal (S_n) as a function of a scan velocity and the integrated signal S.

22. The program storage device of claim 21 wherein the step of calculating the velocity-normalized integrated signal (S_n) comprises:

determining a scan velocity, v; and

dividing the integrated signal S by the scan velocity v.

23. The program storage device of claim 21 wherein the step of calculating the velocity-normalized integrated signal (S_n) comprises:

measuring a channel width (w);

determining a time for traversing the channel width (t); and

computing a velocity-normalized integrated signal according to the equation $S_n = S/(w/t)$.

24. The program storage device of claim 21 wherein the step of calculating the velocity-normalized integrated signal (S_n) comprises subtracting a detector offset S_o from an integrated signal (S).

25. The program storage device of claim 24 wherein a channel width (w) is measured by counting steps in the stepper motor.

* * * * *

"COPYED" 66062007

Sub B3

Sub B4

Subal

Sub B5

Sub B3

5

10

15

20

25

30

35

40

45

50

55

60

65

70

75

80